Bibliographie

Aggarwal, C. C., A. Hinneburg, et D. A. Keim (2001). On the surprising behavior of distance metrics in high dimensional space. *Lecture Notes in Computer Science 1973*, 420–434.

Agrawal, R., T. Imielinski, et A. Swami (1993). Mining association rules between sets of items in large databases. In P. Buneman et S. Jajodia (Eds.), *Proc. of the ACM SIGMOD International Conference on Management of Data*, Washington, USA, pp. 207–216.

Ahmad, K., M. Casey, B. Vrusias, et P. Saragiotis (2003). Combining multiple modes of information using unsupervised neural classifiers. In T. Windeatt et F. Roli (Eds.), *Proc. of International Workshop on Multiple Classifier Systems*, pp. 236–245.

Arigon, M. (2006). *Développements d'outils pour l'aide à l'identification dans les grandes banques de familles de gènes.* Thèse de doctorat, Université Claude Bernard, Lyon, France.

Barthélemy, J.-P. et X. Luong (1987). Sur la topologie d'un arbre phylogénétique : aspects théoriques, algorithmes et applications à l'analyse de données textuelles. *Mathématiques et Sciences Humaines 100*, 57–80.

Barthélemy, J.-P. et X. Luong (1998). Représenter les données textuelles par les arbres. In *Actes de Journées d'Analyse statistique des Données Textuelles (JADT)*, pp. 49–73.

Bauer, H.-U., M. Herrmann, et T. Villmann (1999). Neural maps and topographic vector quantization. *Neural Networks 12*, 659–676.

Bauer, H.-U. et K. Pawelzik (1992). Quantifying the neighborhood preservation of self-organizing feature maps. *IEEE Transactions on Neural Networks 3*, 570–579.

Becker, S. (1995). JPMAX : Learning to recognize moving objects as a model-fitting problem. In G. Tesauro, D. Touretzky, et T. Leen (Eds.), *Advances in Neural Information Processing Systems*, Volume 7, pp. 933–940. MIT Press.

Beckman, R. et R. Cooks (1983). Outliers. *Technometrics 25*, 119–149.

Bellmann, R. (1961). *Adaptive Control Processes : A Guided Tour*. Princeton University Press.

Bengio, Y., O. Delalleau, et N. L. Roux. Volume 18 of *Neural Information Processing*, pp. 107–114. MIT Press.

Benjamini, Y. et Y. Hochberg (1995). Controlling the false discovery rate : a practical and powerful approach to multiple testing. *Journal of the Royal Statistical Society, B 57*, 289–300.

Benjamini, Y. et D. Yekutieli (2001). The control of the false discovery rate in multiple hypothesis testing under dependency. *The Annals of Statistics 29*(1), 1165–1188.

Berglund, E. et J. Sitte (2006). The parameter-less self-organizing map algorithm. *IEEE Transactions on Neural Networks 17*(2), 305–316.

Berthelsen, H. et B. Megyesi (2000). Ensemble of classifiers for noise detection in PoS tagged corpora. In *Proc. of Text, Speech and Dialogue (TSD)*, pp. 27–32.

Beyer, K., J. Goldstein, R. Ramakrishnan, et U. Shaft (1999). When is "nearest neighbor" meaningful ? *Lecture Notes in Computer Science 1540*, 217–235.

Blake, C. et C. Merz (1998). UCI repository of machine learning databases. University of California, Irvine, Dept. of Information and Computer Sciences [inline]. http ://archive.ics.uci.edu/ml/.

Blum, A. et T. Mitchell (1998). Combining labeled and unlabeled data with co-training. In *Proc. of the Workshop on Computational Learning Theory (COLT)*, pp. 92–100. Morgan Kaufmann Publishers.

Bodt, E., M. Cottrell, et M. Verleysen (2002). Statistical tools to access the reliability of the self organizing maps. *Neural Network 15*, 967–978.

Borgelt, C. Recursion pruning for the Apriori algorithm. In *Proc. of 2nd Workshop of Frequent Item Set Mining Implementations (FIMI 2004)*, Brighton, UK, pp. 126–127. CEUR Workshop Proceedings.

Borgelt, C. et R. Kruse (2002). Induction of association rules : Apriori implementation. In *Proc. of the 15th Conference on Computational Statistics (COMPSTAT 2002)*, Heidelberg, Germany. Physika Verlag.

Breiman, L. (1996). Bagging predictors. *Machine Learning 24*(2), 123–140.

Breiman, L. (2001). Random forests. *Machine Learning 45*(1), 5–32.

Brin, S. (1995). Near neighbor search in large metric spaces. In *Proc. of 21th International Conference on Very Large Data Bases (VLDB)*, pp. 574–584.

Brodley, C. E. et M. A. Friedl (1996). Identifying and eliminating mislabeled training instances. In *Proc. of the Innovative Applications of Artificial Intelligence Conference (IAAI)*, Volume 1, pp. 799–805.

Brodley, C. E. et M. A. Friedl (1999). Identifying mislabeled training data. *11*(11), 131–167.

Brown, G. (2005). Managing diversity in regression ensembles. *Journal of Machine Learning Research 6*, 1621–1650.

Chapelle, O., B. Schölkopf, et A. Zien (Eds.) (2006). *Semi-Supervised Learning*. MIT Press.

Chauchat, J.-H. et R. Rakotomalala (2000). *Instance Selection and Construction for Data Mining*, Chapter Sampling Strategy for Building Decision Trees from Very Large Databases Comprising Many Continuous Attributes, pp. 171–188. Kluwer Academic Publishers.

Clech, J. (2004). *Contribution Méthodologique à la Fouille de Données Complexes*. Thèse de doctorat, Université Lyon 2, Lyon, France.

Cliff, A. D. et J. K. Ord (1981). *Spatial processes, models & applications*. London : Pion Limited.

Condorcet, N. (1785). *Essai sur l'application de l'analyse à la probabilité des décisions rendues à la pluralité des voix*. Paris, France : Imprimerie Royale.

Cover, T. M. et P. E. Hart (1967). Nearest neighbor pattern classification. *IEEE Transactions on Information Theory 13*, 21–27.

Darmont, J. (2006). *Optimisation et évaluation de performance pour l'aide à la conception et à l'administration des entrepôts de données complexes*. Habilitation à diriger des recherches, Université Lyon 2.

Demartines, P. (1994). *Analyse de données par réseaux de neurones auto-organisés*. Thèse de doctorat, Institut National Polytechnique de Grenoble, Grenoble, France.

Demartines, P. et J. Hérault (1997). Curvilinear component analysis : a self-organizing neural network for nonlinear mapping of data sets. *IEEE Transactions on Neural Networks 8*(1), 148–154.

Dietterich, T. G. (1998). Approximate statistical tests for comparing supervised classification learning algorithms. *Neural Computation 10*(7), 1895–1924.

Dietterich, T. G. (2000). Ensemble methods in machine learning. *Lecture Notes in Computer Science 1857*, 1–15.

Dietterich, T. G. et G. Bakiri (1991). Error-correcting output codes : a general method for improving multiclass inductive learning programs. In T. L. Dean et K. McKeown (Eds.), *Proc. of the Ninth AAAI Conference on Artificial Intelligence*, Menlo Park, CA, pp. 572–577. AAAI Press.

Doherty, K., R. Adams, et N. Davey (2004). Non-euclidean norms and data normalisation. In M. Verleysen (Ed.), *Proc. of European Symposium on Artificial Neural Networks (ESANN 2004)*, pp. 181–186. d-side publications.

Donoho, D. (2000). High-dimensional data analysis : the curses and blessings of dimensionality. In *American Mathematical Society Conference on Mathematical Challenges of the 21st Century, [inline], http ://www-stat.stanford.edu/∼donoho/.*

Dunau, J.-L. et J.-B. Hiriart-Urruty (2003). Quand le cochonnet n-dimensionnel déborde de sa boîte. *Bulletin de l'Association des Professeurs de Mathématiques de l'Enseignement Public 444*, 84–86.

Efron, B. (1979). Bootstrap methods : Another look at the jacknkife. *Annals of statistics 7*, 1–26.

Fawcett, T. et F. Provost (1997). Adaptive fraud detection. *Data Mining and Knowledge Discovery 1*, 291–316.

Fayyad, U., G. Piatetsky-shapiro, et P. Smyth (1996). Knowledge discovery and data mining : Towards a unifying framework. In *Proc. of the 2nd International Conference on Knowledge Discovery and Data Mining*, pp. 82–88. AAAI Press.

Fessant, F. et P. Aknin (2000). Classification de défauts de rail à l'aide de cartes auto-organisatrices supervisées. In *Neuro-Science et Sciences de l'Ingénieur, [inline], http ://www.inrets.fr/ur/ltn/poles/diag/pdf/NSI00.pdf.*

Fessant, F., P. Aknin, L. Oukhellou, et S. Midenet (2001). Comparison of supervised self-organizing maps using euclidian or mahalanobis distance in classification context. In *Proc. of International Work-Conference on Artificial Neural Networks*, London, UK, pp. 637–644. Springer-Verlag.

Fonseca, C. et P. Fleming (1993). Genetic algorithms for multi-objective optimization : formulation, discussion and generalization. In *Proc of the fifth International Conference on Genetic Algorithms*, pp. 416–423.

Fortune, S. (1987). A sweepline algorithm for Voronoi diagrams. *Algorithmica 2*, 153–174.

Francois, D., V. Wertz, et M. Verleysen (2005). Non-euclidean metrics for similarity search in noisy datasets. In *Proc. of European Symposium on Artificial Neural Networks (ESANN 2005)*, Bruges, Belgium, pp. 70–81.

Freitas, A. (2000). Understanding the crucial difference between classification and discovery of association rules. *SIGKDD Explorations 2*, 65–69.

Freund, Y. (1999). An adaptive version of the boost by majority algorithm. In *Proc. of the 12th Annual Conference on Computational Learning Theory*, New York, USA, pp. 102–113. ACM Press.

Freund, Y. et R. Schapire (1998). Large margin classification using the perceptron algorithm. In *Proc. of the 11th Annual Conference on Computational Learning Theory*, pp. 209–217.

Freund, Y. et R. E. Schapire (1995). A decision-theoretic generalization of on-line learning and an application to boosting. In *Proc. of the 2nd European Conference on Computational Learning Theory (EuroCOLT'95)*, London, UK, pp. 23–37. Springer-Verlag.

Freund, Y. et R. E. Schapire (1996). Experiments with a new boosting algorithm. In *Proc. of the Thirteenth International Conference on Machine Learning (ICML)*, pp. 148–156. Morgan Kaufmann.

Friedman, J. H. et U. Fayyad (1997). On bias, variance, 0/1-loss, and the curse-of-dimensionality. *Data Mining and Knowledge Discovery 1*, 55–77.

Fritzke, B. (1994). Fast learning with incremental RBF networks. *Neural Processing Letters 1* (1), 1–5.

Fritzke, B. (1995). A growing neural gas network learns topologies. In G. Tesauro, D. S. Touretzky, et T. K. Leen (Eds.), *Advances in Neural Information Processing Systems*, Volume 7, Cambridge, MA, pp. 625–632. MIT Press.

Gabriel, K. et R. Sokal (1969). A new statistical approach to geographic variation analysis. *Systematic Zoology 18*, 259–278.

Gama, J. et P. Brazdil (2000). Cascade generalization. *Machine Learning 41* (3), 315–343.

Ge, Y., S. Dudoit, et T. Speed (2003). Resampling-based multiple testing for microarray data analysis. *TEST 12* (1), 1–77.

Geman, S., E. Bienenstock, et R. Doursat (1992). Neural networks and the bias/variance dilemma. *Neural Computing 4* (1), 1–58.

Getis, A. (1991). Spatial interaction and spatial autocorrélation : A cross product approach. *Environment and planning 23*, 1269–1277.

Giné, E. et J. Zinn (1984). Bootstrapping general empirical measures. *Annals of probability 18*, 851–869.

Goldberg, D. E. (1989). *Genetic Algorithms in Search, Optimization and Machine Learning*. Addison-Wesley Longman Publishing Co., Inc.

Golub, T. R., D. K. Slonim, P. Tamayo, C. Huard, M. Gaasenbeek, J. P. Mesirov, H. Coller, M. L. Loh, J. R. Downing, M. A. Caligiuri, C. D. Bloomfield, et E. S. Lander (1999). Molecular classification of cancer : class discovery and class prediction by gene expression monitoring. *Science 286*(5439), 531–537.

Gras, R. (1979). *Contribution à l'étude expérimentale et à l'analyse de certaines acquisitions cognitives et de certains objectifs didactiques en mathématiques.* Thèse détat, Université de Rennes I.

Gras, R., P. Kuntz, R. Couturier, et F. Guillet (2001). Une version entropique de l'intensité d'implication pour les corpus volumineux. *Extraction des connaissances et apprentissage (Actes de EGC 2001) 1*(1), 69–80.

Guérif, S., Y. Bennani, et C. Baudoin (2006). Connectionist and Ethological Approaches for Discovering Salient Facial Movement Features in Human Gender Recognition. In *Proceeding of the 28th International Conference Information Technology Interfaces*, Cavtat, Croatia, pp. 189–194.

Gutierrez-Rios, R. M., D. A. Rosenblueth, J. A. Loza, A. M. Huerta, J. D. Glasner, F. R. Blattner, et J. Collado-Vides (2003). Regulatory network of escherichia coli : Consistency between literature knowledge and microarray profiles. *Genome research 13*(11), 2435–2443.

Hacid, H. (2008). *Un environnement informatique pour l'interrogation et l'accès intelligent aux bases de données complexe.* Thèse de doctorat, Université Lyon 2, Lyon, France.

Herrmann, L. et A. Ultsch (2007). Label propagation for semi-supervised learning in self-organizing maps. In *Proc. of the 6th International Workshop on Self-Organizing Maps (WSOM)*. University Library of Bielefeld, [inline], http ://biecoll.ub.uni-bielefeld.de/volltexte/2007/141/.

Hickernell, F. (1998). A generalized discrepancy and quadrature error bound. *Mathematical Computation 67*, 299–322.

Ho, T. K. (1998). The random subspace method for constructing decision forests. *IEEE Transactions on Pattern Analysis and Machine Intelligence 20*(8), 832–844.

Holm, S. (1979). A simple sequentially rejective multiple test procedure. *Scandinavian Journal of Statistics 6*, 65–70.

Hopke, P. K. et D. L. Massart (1993). Reference data sets for chemometrical methods testing. *Chemometrics and Intelligent Laboratory Systems 19*, 35–41.

Hubel, D. et T. Wiesel (1962). Receptive fields, binocular interaction and functional architecture in the cat's visual cortex. *Journal of physiologie*, 106–154.

Härdle, W., M. Müller, S. Sperlich, et A. Werwatz (2004). Nonparametric density estimation. In *Nonparametric and Semiparametric Models*, Springer Series in Statistics, pp. 39–82. Springer-Verlag.

Hérault, J., A. Guérin-Dugué, et P. Villemain (2002). Searching for the embedded manifolds in high dimensional data, problems and unsolved questions. In *Proc. of the European Symposium on Artificial Neural Networks (ESANN'2002)*, Bruges (Belgium), pp. 173–184.

Jacobs, R., M. Jordan, et A. Barto (1991). Task decomposition through competition in a modular connectionist architecture : The what and where vision tasks. *Cognitive Science 15*, 219–250.

Jain, A. et B. Chandrasekaran (1982). *Classification, pattern recognition and reduction of dimensionality*, Volume 2 of *Handbook of Statistics*, Chapter Dimensionality and sample size considerations in pattern recognition practice, pp. 835–855. Elsevier.

Jain, A., R. Duin, et J. Mao (2000). Statistical pattern recognition : a review. In *IEEE Transaction on Pattern Analysis and Machine Intelligence*, Volume 22, pp. 4–37.

Jain, A. K. et R. C. Dubes (1988). *Algorithms for clustering data*. Upper Saddle River, USA : Prentice-Hall, Inc.

Jaromczyk, J. et G. Toussaint (1992). Relative neighborhood graphs and their relatives. In *Proc. of the IEEE*, Volume 80, New York, USA, pp. 1502–1517. Institute of Electrical and Electronics Engineers.

Kaiser, H. (1958). The varimax criterion for analytic rotation in factor analysis. *Psychometrika 23*, 187–200.

Kearns, M. (1988). Thoughts on hypothesis boosting. Unpublished manuscript, 1988. Project for Ron Rivest's machine learning course at MIT. Included here for historical interest and because it is occasionally cited, [inline], http ://www.cis.upenn.edu/∼mkearns/#publications.

Kearns, M. (1993). Efficient noise-tolerant learning from statistical queries. In *Proc. of the Twenty-Fifth Annual ACM Symposium on Theory of Computing*, pp. 392–401.

Khardon, R. et G. Wachman (2007). Noise tolerant variants of the perceptron algorithm. *Journal of Machine Learning Research 8*, 227–248.

Kira, K. et L. A. Rendell (1992). The feature selection problem : Traditional methods and a new algorithm. In *Proc. of the Tenth National Conference on Artificial Intelligence (AAAI)*, Cambridge, MA, USA, pp. 129–134. AAAI Press and MIT Press.

Kohonen, T. (1982). Self-organized formation of topologically correct feature maps. *Biological Cybernetics 43*, 59–69.

Kohonen, T. (1990). Improved versions of learning vector quantization. In *Proc. of International Joint Conference on Neural Networks*, Volume 1, pp. 545–550.

Kohonen, T. (2001). *Self-organizing maps*, Volume 30 of *Springer Series in Information Sciences*. Springer.

Kohonen, T., J. Hynninen, J. Kangas, et J. Laaksonen (1996). SOM-PAK : The self-organizing map program package. Technical Report A31, Helsinki University of Technology, Laboratory of Computer and Information Science, FIN-02150 Espoo, Finland.

Kong, E. B. et T. G. Dietterich (1995). Error-correcting output coding corrects bias and variance. In *Proc. of the Twelfth International Conference on Machine Learning*, pp. 313–321. Morgan Kaufmann.

Krogh, A. et J. Vedelsby (1995). Neural network ensembles, cross validation, and active learning. In G. Tesauro, D. Touretzky, et T. Leen (Eds.), *Proc. of Advances in Neural Information Processing Systems*, Volume 7, pp. 231–238. The MIT Press.

Kruskal, J. B. (1956). On the shortest spanning subtree of a graph and the travelling salesman problem. In *Proc. of American Mathematical Society*, Volume 7, pp. 48–50.

Kuncheva, L. et C. Whitaker (2001). Ten measures of diversity in classifier ensembles : limits for two classifiers. In *Proc. of Workshop on Intelligent Sensor Processing*, pp. 1–10.

Kuncheva, L. et C. Whitaker (2003). Measures of diversity in classifier ensembles and their relationship with the ensemble accuracy. *Machine Learning 51*(2), 181–207.

Lagus, K., S. Kaski, et T. Kohonen (2004). Mining massive document collections by the WEBSOM method. *Information Sciences 163*(1–3), 135–156.

Lallich, S. (2002). *Mesure et validation en extraction des connaissances à partir des données*. Habilitation à diriger les recherches, Université Lumière Lyon 2, Lyon : France.

Lallich, S., F. Muhlenbach, et J.-M. Jolion (2003a). A test to control a region growing process within a hierarchical graph. *Pattern Recognition 36*, 2201–2211.

Lallich, S., F. Muhlenbach, et D. Zighed (2003b). Traitement des exemples atypiques en apprentissage par la régression. *Revue des Sciences et Technologies de l'Information (RSTI) 17*, 399–410.

Lallich, S., E. Prudhomme, et O. Teytaud (2004). Contrôle du risque multiple en sélection de règles d'association significatives. In *Extraction des connaissances et apprentissage (Actes de EGC 2004)*, Volume 2 of *RNTI*, Toulouse, pp. 305–316. Cépaduès Editions.

Lallich, S. et O. Teytaud (2004). Evaluation et validation de l'intérêt des règles d'association. *Mesures de qualité pour la fouille des données*, 193–218.

Lallich, S., O. Teytaud, et E. Prudhomme (2006a). *Association rules interestingness : measure and validation.* Quality Measures in Data Mining. Heidelberg, Germany : Springer.

Lallich, S., O. Teytaud, et E. Prudhomme (2006b). Statistical inference and data mining : false discoveries control. In *Proc. of the 17th Conference on Computational Statistics (COMPSTAT)*, Rome, Italy, pp. 325–336.

Lebart, L., A. Morineau, et M. Piron (1997). *Statistique exploratoire multidimensionnelle.* Paris : Dunod.

Lenca, P., P. Meyer, P. Picouet, B. Vaillant, et S. Lallich (2003). Critères d'évaluation des mesures de qualité en ECD. *Entreposage et Fouille de données* (1), 123–134.

Lerman, I. et J. Azé (2003). Une mesure probabiliste contextuelle discriminante de qualité des règles d'association. *RSTI-RIA (EGC 2003) 1* (17), 247–262.

Lerman, I., R. Gras, et H. Rostam (1981). Elaboration et évaluation d'un indice d'implication pour les données binaires, I et II. *Mathématique et Sciences Humaines* (74, 75), 5–35, 5–47.

Leskes, B. et L. Torenvliet (2008). The value of agreement a new boosting algorithm. *Journal of Computer and System Sciences 74*(4), 557–586.

Liu, B., W. Hsu, et Y. Ma (1998). Integrating classification and association rule mining. In *Proc. of new directions in rough sets, data mining, and granular-soft computing*, pp. 80–86. Springer.

Liu, Y. et X. Yao (1999). Ensemble learning via negative correlation. *Neural Networks 12*, 1399–1404.

Mantel, N. (1967). The detection of disease clustering and a general regression approach. *Cancer Research 27*, 209–220.

Martinetz, T. M. et K. J. Schulten (1991). *Artificial Neural Networks*, Chapter A neural-gas network learns topologies, pp. 397–402. Amsterdam, North-Holland.

Martinetz, T. M. et K. J. Schulten (1994). Topology representing networks. *Neural Networks 7*(3), 507–522.

Mayaffre, D. (2003). Les discours de Jacques Chirac (1995-2002). représentation arborée et généalogie politique. *Histoire et mesure 18*(3–4), 289–311.

McQueen, J. (1967). Some methods for classification and analysis of multivariate observations. In *Proc. of the Fifth Berkeley Symposium on Mathematical Statistics and Probability*, Volume 1, pp. 281–297.

Midenet, S. et A. Grumbach (1994). Learning associations by self-organisation : the LASSO model. *Neurocomputing 6*, 343–361.

Moody, J. E. et C. Darken (1989). Fast learning in networks of locally-tuned processing units. *Neural Computation 1*, 281–294.

Muhlenbach, F. (2002). *Évaluation de la qualité de la représentation en fouille de données.* Th'ese de doctorat, Université Lyon 2, Lyon, France.

Muhlenbach, F., S. Lallich, et D. Zighed (2003). Identifying and handling mislabelled instances. *Journal of Information Intelligent Systems 22*, 89–109.

Newman, L. et T. Polk (2007). The emergence of semantic topography in a neurally-inspired computational model. In *Proc. of 8th International Conference on Cognitive Modeling, [inline], http ://sitemaker.umich.edu/iccm2007.org/files/newman_ _ _polk.pdf.*

Oliveira, L. S., M. Morita, R. Sabourin, F. Bortolozzi, et C. Paraná (2005). Multiobjective genetic algorithms to create ensemble of classifiers. In *Proc. of the Third International Conference on Evolutionary Multi-Criterion Optimization*, pp. 592–606.

Palmer, S. E. (1978). *Cognition and categorization* (Rosch, E. and Lloyd, B. L. ed.)., Chapter Fundamental aspects of cognitive representation., pp. 259–302.

Parsons, L., E. Haque, et H. Liu (2004). Subspace clustering for high dimensional data : a review. *SIGKDD Explor. Newsl. 6*(1), 90–105.

Polani, D. (1997). Organization measures for self-organizing maps. In T. Kohonen (Ed.), *Proceedings of WSOM'97 : Workshop on Self-Organizing Maps*, pp. 280–285.

Polani, D. et T. Uthmann (1993). Training kohonen feature maps in different topologies : An analysis using genetic algorithms. In *Proc. of the 5th International Conference on Genetic Algorithms*, San Francisco, USA, pp. 326–333. Morgan Kaufmann Publishers Inc.

Prim, R. C. (1957). Shortest connection networks and some generalisations. *Bell Systems Technical Journal*, 1389–1410.

Prudhomme, E. et S. Lallich (2005a). Quality measure based on Kohonen maps for supervised learning of large high dimensional data. In *Proc. of International Symposium on Applied Stochastic Models and Data Analysis (ASMDA 2005)*, Brest, France, pp. 246–255.

Prudhomme, E. et S. Lallich (2005b). Validation statistique des cartes de Kohonen en apprentissage supervisé. In *Extraction des connaissances et apprentissage (Actes de EGC 2005)*, Volume 1 of *RNTI-E-3*, pp. 79–90.

Prudhomme, E. et S. Lallich (2007). Ensemble prédicteur fondé sur les cartes auto-organisatrices adaptées aux données volumineuses. In *Extraction des connaissances et apprentissage (Actes de EGC 2007)*, RNTI, Toulouse, pp. 473–484. Cépaduès Editions.

Prudhomme, E. et S. Lallich (2008a). Maps ensemble for semi-supervised learning of large high dimensional datasets. In *Proc. of the 17th International Symposium on Methodologies for Intelligent Systems (ISMIS)*, Toronto, Canada, pp. 100–110.

Prudhomme, E. et S. Lallich (2008b). Optimization of self-organizing maps ensemble in prediction. In *Proc. of International Conference on Data Mining (DMIN'08)*, Las Vegas, USA.

Prudhomme, E. et S. Lallich (2009). *Représentation des données par un comité de cartes auto-organisatrices : une application aux données bruitées.* numéro spécial Apprentissage Artificiel & Fouille de Données (AAFD), à paraître. RNTI.

Quinlan, J. R. (1990). Induction of decision trees. In J. W. Shavlik et T. G. Dietterich (Eds.), *Readings in Machine Learning*. Morgan Kaufmann. Originally published in *Machine Learning* 1 :81–106, 1986.

Rakotomalala, R. (2005). TANAGRA : un logiciel gratuit pour l'enseignement et la recherche. In *Extraction des connaissances et apprentissage (Actes de EGC 2005)*, Volume 2 of *RNTI-E-3*, pp. 697–702.

Rauber, A. (1999). LabelSom : On the labeling of self-organizing maps. In *Proceedings of the International Joint Conference on Neural Networks (IJCNN'99)*, pp. 1–6.

Ritschard, G., D.-A. Zighed, et S. Marcellin (2007). Données déséquilibrées, entropie décentrée et indice d'implication. In *Actes de Nouveaux apports théoriques à l'analyse statistique implicative et applications*, pp. 315–327. Departament de Matematiques, Universitat Jaume I.

Rousset, P., C. Guinot, et J. Vero (2005). Utilisation des cartes d'auto-organisation dans la classification, illustration par des exemples. *Bulletin de méthodologie sociologique 87*, 5–37.

Saitou, N. et M. Nei (1987). Neighbor-joining method. *Molecular Biology and Evolution 4*, 406–425.

Sakakibara, Y. (1993). Noise-tolerant Occam algorithms and their applications to learning decision trees. *Machine Learning 11* (1), 37–62.

Sammon, Jr., J. (1969). A nonlinear mapping for data structure analysis. *IEEE Transactions on Computers 18*(5), 401–409.

SAS (1989). *SAS/STAT user's guide, Version 6, Fourth Edition*, Volume 2. SAS Institute Inc.

Schapire, R. E. (1990). The strength of weak learnability. *Machine Learning 5*(2), 197–227.

Schapire, R. E., Y. Freund, P. Bartlett, et W. S. Lee (1998). Boosting the margin : a new explanation for the effectiveness of voting methods. *Annals of Statistics 26*, 322–330.

Scott, D. W. et J. R. Thompson (1983). Probability density estimation in higher dimensions. In J. Gentle (Ed.), *Computer Science and Statistics : Proc. of the Fifteenth Symposium on the Interface*, pp. 173–179. Elsevier Science Publishers.

Scuturici, M., J. Clech, V.-M. Scuturici, et D.-A. Zighed (2005). Topological representation model for image databases query. *Journal of Experimental and Theoretical Artificial Intelligence 17*(1-2), 145–160.

Sebban, M. et D. A. Zighed (1996). Test de séparabilité des classes dans $\mathbb{R}^p$. In *XXVème colloque des Structures Economiques, Econométrie et Informatique*.

Sharkey, A. et N. Sharkey (1997). Combining diverse neural net. *The Knowledge Engineering Review 12*(3), 231–247.

Shepard, R. et J. Carroll (1965). Parametric representation of nonlinear data structures. In P. R. Krishnaiah (Ed.), *Proc. of International Symposium on Multivariate Analysis*, pp. 561–592. Academic Press.

Song, X.-H. et P. K. Hopke (1996). Kohonen neural network as a pattern recognition method based on the weight interpretation. *Analytica Chimica Acta 334*, 57–66.

Steinbach, M., L. Ertöz, et V. Kumar (2004). The challenges of clustering high-dimensional data. In L. T. Wille (Ed.), *New Vistas in Statistical Physics : Applications in Econophysics, Bioinformatics, and Pattern Recognition*, pp. 273–307. Springer-Verlag.

Storey, J. D. (2002). A direct approach to false discovery rates. *Journal of the Royal Statiscal Society, B 64*, 479–498.

Storey, J. D. et R. Tibshirani (2003). Statistical significance for genomewide studies. In *Proc. of the National Academy of Sciences of the United States of America*, Volume 100, pp. 9440–9445.

Suchier, H.-M. (2006). *Nouvelles Contributions du Boosting en Apprentissage Automatique*. Thèse de doctorat, Université Jean Monnet, Saint-Etienne, France.

Tenenbaum, J. B., V. de Silva, et J. C. Langford (2000). A global geometric framework for nonlinear dimensionality reduction. *Science 290*(5500), 2319–2323.

Teytaud, O., S. Gelly, S. Lallich, et E. Prudhomme (2006). Quasi-random bootstrap, with applications to rule extraction and (sub)bagging, Helsinki, Finland. In *Proc. of International Workshop on Intelligent Information Access (IIIA 2006), [inline], http ://hal.archives-ouvertes.fr/hal-00113368/fr/.*

Thomas, J. (2009). *Apprentissage supervisé de données déséquilibrées par forêt aléatoire.* Thè de doctorat, Université Lyon 2, Lyon :France.

Tibshirani, R. (1996). Regression shrinkage and selection via the lasso. *Journal of the Royal Statistical Society, Series B 58*(1), 267–288.

Ting, K. M. et I. H. Witten (1999). Issues in stacked generalization. *Journal of Artificial Intelligence Research 10*, 271–289.

Toussaint, G. T. et R. Menard (1980). Fast algorithms for computing the planar relative neighborhood graph. In *Methods of Operations Research, Proc. of the Fifth Symposium on Operations Research*, pp. 425–428.

Trunk, G. (1979). A problem of dimensionality : a simple example. In *IEEE Transaction on Pattern Analysis and Machine Intelligence*, Volume 1, pp. 306–307.

Tumer, K. et J. Gosh (1995). Theoretical foundations of linear and order statistics combiners for neural pattern classifiers. Technical report, Computer and Vision Research Center, University of Texas, Austin, USA, [inline], ftp ://ftp.lans.ece.utexas.edu/pub/papers/theory_comb_tr.ps.Z.

Ueda, N. et R. Nakano (1996). Generalization error of ensemble estimators. In *Proc. of International Conference on Neural Networks (ICNN 96)*, Volume 1, pp. 90–95.

Ultsch, A. et L. Herrmann (2005). The architecture of emergent self-organizing maps to reduce projection errors. In *Proc. of European Symposium on Artificial Neural Network (ESANN)*, pp. 1–6.

Ultsch, A. et H. Siemon (1990). Kohonen's self organizing feature maps for exploratory data analysis. In K. academic Publishers (Ed.), *Proc. of International Neural Network Conference (INNC'90)*, pp. 305–308.

Vaillant, B., P. Meyer, E. Prudhomme, S. Lallich, P. Lenca, et S. Bigaret (2005). Mesurer l'intérêt des règles d'association. In *Atelier Qualité des Données et des Connaissances (DQK 05, Actes de EGC 2005)*, pp. 69–78.

Vaillant, B., P. Picouet, et P. Lenca (2003). An extensible platform for rule quality measure benchmarking. In R. Bisdorff (Ed.), *Proc. of Human Centered Processes (HCP'2003)*, Luxembourg, pp. 187–191.

Valiant, L. G. (1984). A theory of the learnable. *Commun. ACM 27*(11), 1134–1142.

van der Corput, J. G. (1935). Verteilungsfunktionen. In *Proc. of Ned. Akad. v. Wet.*, Volume 38, pp. 813–821.

van der Maaten, L. et G. Hinton (2008). Visualizing data using t-SNE. *Journal of Machine Learning Research 9*, 2579–2605.

Van Der Vaart, A. et J. Wellner (1996). *Weak Convergence and Empirical Processes*. Springer Series in Statistics. Springer-Verlag Publishers.

Vapnik, V. (1998). *Statistical Learning Theory*. Wiley :New York.

Verbaeten, S. et A. Van Assche (2003). Ensemble methods for noise elimination in classification problems. In *Proc. of International Workshop on Multiple Classifier Systems*, pp. 317–325. Springer.

Verleysen, M. (2003). *Limitations and future trends in neural computation*, Chapter Learning high-dimensional data, pp. 141–162. IOS Press.

Verleysen, M., D. François, G. Simon, et V. Wertz (2003). On the effects of dimensionality on data analysis with neural networks. In J. Mira et J. Alvarez (Eds.), *Computational Methods in Neural Modeling, Proc. of International Work-Conference on Artificial and Natural Neural Networks*, Volume II, pp. 105–112. Springer-Verlag.

Vesanto, J. et E. Alhoniemi (2000). Clustering of the self-organizing map. In *IEEE Transactions On Neural Networks*, Volume 11, pp. 586–600.

Villmann, T. et J. C. Claussen (2006). Magnification control in self-organizing maps and neural gas. *Neural Computation 18*(2), 446–469.

Villmann, T., R. Der, et T. Martinetz (1994). A novel approach to measure the topology preservation of feature maps. In M. Marinaro et P. G. Morasso (Eds.), *Proc. of the International Conference on Artificial Neural Networks*, pp. 298–301. Springer Verlag.

von Der Malsburg, C. (1973). Self-organisation of orientation sensitive cells in the striate cortex. *Kybernetik 14*, 85–100.

Ward, J. H. (1963). Hierarchical grouping to optimize an objective function. *Journal of American Statistical Association 58*(301), 236–244.

Weber, R., H.-J. Schek, et S. Blott (1998). A quantitative analysis and performance study for similarity-search methods in high-dimensional spaces. In *Proc. of 24th International Conference on Very Large Data Bases (VLDB)*, pp. 194–205.

Westfall, P. et S. Young (1993). *Resampling based multiple testing : examples and methods for p-values adjustment*. John Wiley & Sons.

Wilkinson, J. H. et C. Reinsch (1971). *Linear algebra, vol. II, handbook for automatic computation*. New-York, USA : Springer-Verlag.

Willshaw, D. J. et C. von der Malsburg (1976). How patterned neural connections can be set up by self-organization. *Royal Society of London Proceedings Series B 194*, 431–445.

Wilson, D. (1972). Asymptotic properties of nearest neighbor rules using edited data. *IEEE Transaction on Systems, Man and Cybernetics 2*, 408–421.

Windeatt, T. et R. Ghaderi (2003). Coding and decoding strategies for multi-class learning problems. *Information Fusion 4*(1), 11–21.

Wolpert, D. H. (1992). Stacked generalization. *Neural Networks 5*(2), 241–259.

Zanda, M., G. Brown, G. Fumera, et F. Roli (2007). Ensemble learning in linearly combined classifiers via negative correlation. In *Proc. of International Workshop on Multiple Classifier Systems*, pp. 440–449.

Zhou, Y. et S. Goldman (2004). Democratic co-learning. Volume 00, Los Alamitos, USA, pp. 594–202. IEEE Computer Society.

Zhou, Z.-h., J. Wu, W. Tang, et Z. qian Chen (2002). Selectively ensembling neural classifiers. In *Proc. of the 2002 International Joint Conference on Neural Networks (IJCNN'02)*, pp. 1411–1415.

Zhou, Z.-h., J. xin Wu, Y. Jiang, et S. fu Chen (2001). Genetic algorithm based selective neural network ensemble. In *Proc. of the 17th International Joint Conference on Artificial Intelligence (IJCAI)*, pp. 797–802. Morgan Kaufmann.

Zhu, X. (2005). Semi-supervised learning literature survey, tech. report 1530, department of computer sciences, university of wisconsin, madison, usa. [inline]. http ://pages.cs.wisc.edu/ jerryzhu/research/ssl/semireview.html. Technical report.

Zhu, X., Z. Ghahramani, et J. Lafferty (2003). Semi-supervised learning using gaussian fields and harmonic functions. In *Proc. of the 20th International Conference in Machine Learning (ICML)*, pp. 912–919.

Zighed, D. A., S. Lallich, et F. Muhlenbach (2001). Séparabilité des classes dans $\mathbb{R}^p$. In *Actes du VIIIe Congrès de la Société Francophone de Classification (SFC'01)*, pp. 356–363.

Zighed, D. A., S. Lallich, et F. Muhlenbach (2002). Separability index in supervised learning. In H. M. e. H. T. T. Elomaa (Ed.), *Principles of Data Mining and Knowledge Discovery, Proc. of the 6th European Conference on Principles and Practice of Knowledge Discovery in Databases*, pp. 475–487. Springer-Verlag.

Zupan, J., M. Novic, X. Li, et J. Gasteiger (1994). Classification of multicomponent analytical data of olive oils using different neural networks. *Analytica Chimica Acta 292*, 219–234.