Bibliographie

[Abadeh et al., 2007] Abadeh, M. S., Habibi, J., Barzegar, Z., and Sergi, M. (2007). A parallel genetic local search algorithm for intrusion detection in computer networks. *Engineering Applications of Artificial Intelligence*, 20(8) :1058 – 1069.

[Agrawal and Srikant, 1994] Agrawal, R. and Srikant, R. (1994). Fast algorithms for mining association rules. In Bocca, J. B., Jarke, M., and Zaniolo, C., editors, *Proc. 20th Int. Conf. Very Large Data Bases, VLDB*, pages 487–499. Morgan Kaufmann.

[Anderson et al., 1994] Anderson, D., Frivold, T., Tamaru, A., and Valdes, A. (May 1994). Next generation intrusion detection expert system (nides). *Software Users Manual, Beta-Update Release, Computer Science Laboratory, SRI International, Menlo Park, CA, USA*, Technical Report SRI-CSL-95-0 :222–232.

[Anderson et al., 1995] Anderson, D., Lunt, T., Tamaru, A., and Valdes, A. (May 1995). Detecting unusual program behavior using the statistical component of the next generation intrusion detection expert system (nides). *Software Users Manual, Beta-Update Release, Computer Science Laboratory, SRI International, Menlo Park, CA, USA*, Technical Report SRI-CSL-95-06 :222–232.

[Anderson, 1980] Anderson, J. (1980). Computer security threat monitoring and surveillance. *James P. Anderson Company, Fort Washington, Pennsylvania*.

[Bahri and Lallich, 2009b] Bahri, E. and Lallich, S. (2009b). Pruning for Extracting Class Association Rules without Candidate. *The 2009 International Conference on Data Mining , DMIN 2009, Las vegas, USA*.

[Bahri and Lallich, 2010] Bahri, E. and Lallich, S. (2010). Proposition d'une méthode de classification associative adaptative. *10ème Journées Francophones d'Extraction et Gestion des Connaissances, EGC 2010, Hammamet*, pages 501–512.

[Bahri and Lallich, 2009a] Bahri, E. and Lallich, S. (Mai, 2009a). Pour une classification associative plus efficace. *9ème Conférence francophone sur l'apprentissage artificiel, CAP 09, Hammamet, Tunisie*.

[Bahri et al., 2009] Bahri, E., Lallich, S., Nicoloyannis, N., and Maddouri, M. (2009). A hybrid approach of *Boosting* against noisy data, mining complex data. *Studies in Computational Intelligence (Eds.) : Mining Complex Data*, 165(41-54) :225–254.

[Bahri and Maddouri, 2008] Bahri, E. and Maddouri, M. (Janvier 2008). Nouvelle approche du *Boosting* pour les données bruitées. *8ème Conférence Extraction et Gestion des Connaissances (EGC 08)*, Revue des Nouvelles Technologies de l'Information, Cépaduès, Sofia Antipolis :349–360.

[Bauer and Kohavi, 1999] Bauer, E. and Kohavi, R. (1999). An empirical comparison of voting classification algorithms : Bagging, *Boosting*, and variants. *Machine Learning*, 24 :173–202.

[Bazan et al., 2004] Bazan, J. G., Nguyen, H. S., and Szczuka, M. S. (2004). A view on rough set concept approximations. *Fundam. Inform.*, 59(2-3) :107–118.

[Benanni, 2006] Benanni, Y. (2006). *Apprentissage Connexionniste*. Editions Hermès Science.

[Benjamini and Liu, 1999] Benjamini, Y. and Liu, W. (1999). A step-down multiple-hypothesis procedure that controls the false discovery rate under independance. *Stat Planning Inference*, 82 :163–170.

[Bidan et al., 2006] Bidan, C., Hiet, G., Mé, L., Morin, B., and Zimmermann, J. (Octobre 2006). Vers une détection d'intrusions à fiabilité et pertinence prouvables. *Revue de l'Electricité et de l'Electronique (REE)*, 9.

[Breiman, 1996] Breiman, L. (1996). Bagging predictors. *Machine Learning*, 26 :123–140.

[Breiman, 1998] Breiman, L. (1998). Arcing classifiers. *Annals of statistics*, 26 :801–849.

[Breiman, 2001a] Breiman, L. (2001a). Random forests. *Machine Learning*, 45 :5–32.

[Breiman, 2001b] Breiman, L. (2001b). Some infinity theory for predictor ensembles. *Tech. Rep. No. 579, Berkeley : Department of Statistics, University of California*.

[Breiman et al., 1984] Breiman, L., Friedman, J. H., Olshen, R. A., and Stone, C. J. (1984). *Classification and Regression Trees*. Statistics/Probability Series. Wadsworth Publishing Company, Belmont, California, U.S.A.

[Breiman et al., 1984] Breiman, L., Friedman, J. H., Olshen, R. A., and Stone, C. J. (1984). Classification and regression trees. technical report. *Wadsworth International, Monterey, CA*.

[Brodley and Friedl, 1996] Brodley, C. E. and Friedl, M. A. (1996). Identifying and eliminating mislabeled training instances. In *AAAI/IAAI, Vol. 1*, pages 799–805.

[Cannady, 1998] Cannady, J. (1998). Artificial neural networks for misuse detection. In *National Information Systems Security Conference*, pages 443–456.

[Chawla, 2003] Chawla, N. (2003). C4.5 and imbalanced datasets :investigating the effect of sampling method, probabilistic estimate, and decision tree structure. *ICML'Workshop on Learning from Imbalanced Data Sets*.

[Chawla and Kolcz, 2003] Chawla, N., N. J. and Kolcz, A. (2003). *ICML'Workshop on Learning from Imbalanced Data Sets*.

[Chawla and Kolcz, 2004] Chawla, N., N. J. and Kolcz, A. (2004). Special issue on class imbalances. *SIGKDD Explorations*, 6.

[Chawla et al., 2002] Chawla, N. V., Bowyer, K. W., Hall, L. O., and Kegelmeyer, W. P. (2002). Smote : Synthetic minority over-sampling technique. *J. Artif. Intell. Res. (JAIR)*, 16 :321–357.

[Chen and Breiman, 2004] Chen, C., A. L. and Breiman, L. (2004). Using random forest to learn imbalanced data. Technical report, Berkeley, Department of Statistics, University of California.

[Clark and Boswell, 1991] Clark, P. and Boswell, R. (1991). Rule induction with cn2 : Some recent improvements. pages 151–163. Springer-Verlag.

[Clark and Niblett, 1989] Clark, P. and Niblett, T. (1989). The cn2 induction algorithm. In *Machine Learning*, pages 261–283.

[Coenen, 2003a] Coenen, F. (2003a). The LUCS-KDD discretised/normalised ARM and CARM Data Library. *Department of Computer Science, The University of Liverpool, UK*.

[Coenen, 2003b] Coenen, F. (2003b). The LUCS-KDD software library. *http ://www.csc.liv.ac.uk/ frans/KDD/Software*.

[Cohen, 1995] Cohen, W. (1995). Fast effective rule induction. In *In Proceedings of the Twelfth International Conference on Machine Learning*, pages 115–123. Morgan Kaufmann.

[Cornuéjols et al., 2003] Cornuéjols, A., Miclet, L., and Kodratoff, Y. (2003). Apprentissage Artificiel : Concepts et Algorithmes. *Editions Eyrolles*.

[Debar and Siboni, 1992] Debar, H., B. M. and Siboni, D. (1992). A neural network component for an intrusion detection system. *Proceedings of the IEEE Symposium of Research in Computer Security and Privacy*.

[Denning, 1987] Denning, D. E. (1987). An intrusion detection model. *IEEE Transaction on Software Engineering*, SE-13(2) :222–232.

[Denning and Neumann, 1985] Denning, D. E. and Neumann, P. (Menlo Park 1985). Requirement and model for ides- a real-time intrusion detection system. *Computer Science Laboratory, SRI International*, Technical Report 83F83-01-00 :222–232.

[Dietterich, 1999] Dietterich, T. G. (1999). An experimental comparison of three methods for constructing ensembles of decision trees : bagging, boosting, and randomization. *Machine Learning*, pages 1–22.

[Dietterich, 2000] Dietterich, T. G. (2000). Ensemble methodes in machine learning. *First International Workshop on Multiple ClassifierSystems*, pages 1–15.

[Domingo and Watanabe, 2000] Domingo, C. and Watanabe, O. (2000). MadaBoost : A modification of AdaBoost. In *Proc. 13th Annu. Conference on Comput. Learning Theory*, pages 180–189. Morgan Kaufmann, San Francisco.

[Domingos, 1999] Domingos, P. (1999). Metacost : a general method for making classifiers cost-sensitive. In *KDD '99 : Proceedings of the fifth ACM SIGKDD international conference on Knowledge discovery and data mining*, pages 155–164, New York, NY, USA. ACM.

[Dong and Li, 1999] Dong, G. and Li, J. (1999). Efficient mining of emerging patterns : discovering trends and differences. In *KDD '99 : Proceedings of the fifth ACM SIGKDD international conference on Knowledge discovery and data mining*, pages 43–52, New York, NY, USA. ACM.

[Dong et al., 1999] Dong, G., Zhang, X., Wong, L., and Li, J. (1999). CAEP : Classification by Aggregating Emerging Patterns. In *Discovery Science*, pages 30–42.

[Du et al., 2007] Du, J., Cai, Z., and Ling, C. X. (2007). Cost-sensitive decision trees with pre-pruning. In *Canadian Conference on AI*, pages 171–179.

[Duda et al., 2001] Duda, R. O., Hart, P. E., and Stork, D. G. (2001). *Pattern Classification*. Wiley, New York, 2. edition.

[Efron, 1979] Efron, B. (1979). Bootstrap methods : Another look at the jackknife. *Ann. Statist*, 7 :1–26.

[Ertèz et al., 2004] Ertèz, L., Eilertson, E., Lazarevic, A., Kumar, P.-N., Srivastava, V., and Dokas, P. (2004). The MINDS - Minnesota intrusion detection system. *Next Generation Data Mining, MIT Press*.

[Estabrooks and Japkowicz, 2001] Estabrooks, A. and Japkowicz, N. (2001). A mixture-of-experts framework for learning from imbalanced data sets. In *IDA '01 : Proceedings of the 4th International Conference on Advances in Intelligent Data Analysis*, pages 34–43, London, UK. Springer-Verlag.

[Fan et al., 1999] Fan, W., Stolfo, S. J., Zhang, J., and Chan, P. K. (1999). Adacost : misclassification cost-sensitive *Boosting*. *In Proceedings of the Sixteenth International Conference on Machine Learning*, pages 99–105.

[Flouvat et al., 2006] Flouvat, F., Marchi, F. D., and Petit, J.-M. (2006). Vers le prototypage rapide de programmes de fouille de données. In *BDA*.

[Forrest et al., 1996] Forrest, S., Hofmeyr, S. A., Somayaji, A., and Longstaff, T. A. (1996). A sense of self for unix processes. In *IEEE Symposium on Security and Privacy*, pages 120–128, Los Alamitos, CA. IEEE Computer Society Press.

[Freund, 2000] Freund, Y. (2000). An adaptive version of the boost by majority algorithm. In *In Proceedings of the Twelfth Annual Conference on Computational Learning Theory*, pages 102–113.

[Freund and Schapire, 1996] Freund, Y. and Schapire, R. (1996). Experiments with a new *Boosting* algorithm. *In Machine Learning : Proceedings of the Thirteenth National Conference*, pages 148–156.

[Freund and Schapire, 1997] Freund, Y. and Schapire, R. E. (1997). A decision-theoretic generalization of on-line learning and an application to *Boosting*. *J. Comput. Syst. Sci.*, 55(1) :119–139.

[Friedman et al., 1998] Friedman, J., Hastie, T., and Tibshirani, R. (1998). Additive logistic regression : a statistical view of *Boosting*. *Dept. of Statistics, Stanford University Technical Report*.

[Friedman, 1999] Friedman, J. H. (1999). Stochastic gradient *Boosting*. *Computational Statistics and Data Analysis*, 38 :367–378.

[Friedman, 2000] Friedman, J. H. (2000). Greedy function approximation : A gradient *Boosting* machine. *Annals of Statistics*, 29 :1189–1232.

[Friedman and Popescu, 2005] Friedman, J. H. and Popescu, B. E. (2005). Predictive learning via rule ensembles. Technical report, Technical report, Dept. of Statistics, Stanford University.

[Garriga et al., 2006] Garriga, G. C., Kralj, P., and Lavrac, N. (2006). Closed sets for labeled data. In *PKDD*, pages 163–174.

[Giacinto et al., 2008] Giacinto, G., Perdisci, R., Del Rio, M., and Roli, F. (2008). Intrusion detection in computer networks by a modular ensemble of one-class classifiers. *Inf. Fusion*, 9(1) :69–82.

[Giacinto et al., 2005] Giacinto, G., Perdisci, R., and Roli, F. (2005). Network intrusion detection by combining one-class classifiers. *International Conference on Image Analysis and Processing, ICIAP*, (Special Session on Intrusion Detection).

[Giacinto and Roli, 2003] Giacinto, G. and Roli, F. (2003). Intrusion detection in computer networks by multiple classifier systems. *proceeding of ICPR, 16th international conference on pattern recognition*, (Quebec City, Canada).

[Grzymala-Busse, 1987] Grzymala-Busse, J. W. (1987). Learning from examples based on rough multisets. In *ISMIS*, pages 325–332.

[Gurley, 2000] Gurley, R. (2000). Intrusion detection. *MacMillan Technical Publishing.*

[Han et al., 2000] Han, J., Pei, J., and Yin, Y. (2000). Mining frequent patterns without candidate generation. In Chen, W., Naughton, J., and Bernstein, P. A., editors, *2000 ACM SIGMOD Intl. Conference on Management of Data*, pages 1–12. ACM Press.

[Hastie et al., 2001] Hastie, T., Tibshirani, R., and Friedman, J. (2001). *The Elements of Statistical Learning.* Springer.

[Hervé et al., 2000] Hervé, D., Marc, D., and Andreas., W. (2000). A revised taxonomy for intrusion detection systems. *Annales des Télécommunications*, 55 :7–8.

[Hofmeyr, 2004] Hofmeyr, S. A. (2004). The implications of immunology for secure systems design. *Computers & Security*, 23(6) :453–455.

[Hong and Michalski, 1986] Hong, J., M.-I. and Michalski, R. S. (May 1986). Aq15 : Incremental learning of attribute-based descriptions from examples, the method and user's guide. ISG 86-5 UIUCDCS-F-86-949, Reports of the Intelligent Systems Group, Department of Computer Science, University of Illinois, Urbana.

[Japkowicz, 2000] Japkowicz, N. (2000). Aaai'workshop on learning from imbalanced data sets. Technical Report WS-00-05, AAAI.

[Japkowicz et al., 1995] Japkowicz, N., Myers, C., and Gluck, M. (1995). A novelty detection approach to classification. In *IJCAI'95 : Proceedings of the 14th international joint conference on Artificial intelligence*, pages 518–523, San Francisco, CA, USA. Morgan Kaufmann Publishers Inc.

[Japkowicz and Stephen, 2002] Japkowicz, N. and Stephen, S. (2002). The class imbalance problem : A systematic study. *Intell. Data Anal.*, 6(5) :429–449.

[Joshi et al., 2001a] Joshi, M. V., Agarwal, R. C., and Kumar, V. (2001a). Mining needle in a haystack : classifying rare classes via two-phase rule induction. *SIGMOD*, 30(2) :91–102.

[Joshi et al., 2002] Joshi, M. V., Agarwal, R. C., and Kumar, V. (2002). Predicting rare classes : can *Boosting* make any weak learner strong. *In Proceedings of the Eighth International Conference on Knowledge Discovery and Data Mining*, pages 297–306.

[Joshi et al., 2001b] Joshi, M. V., Kumar, V., and Agarwal, R. C. (2001b). Evaluating *Boosting* algorithms to classify rare classes : Comparison and improvements. In *ICDM '01 : Proceedings of the 2001 IEEE International Conference on Data Mining*, pages 257–264, Washington, DC, USA. IEEE Computer Society.

[Kruegel et al., 2003] Kruegel, C., Mutz, D., Robertson, W., and Valeur, F. (2003). Bayesian event classification for intrusion detection. In *ACSAC '03 : Proceedings of the 19th Annual Computer Security Applications Conference*, page 14, Washington, DC, USA. IEEE Computer Society.

[Kubat et al., 1998a] Kubat, M., Holte, R. C., and Matwin, S. (1998a). Machine learning for the detection of oil spills in satellite radar images. *Mach. Learn.*, 30(2-3) :195–215.

[Kubat et al., 1998b] Kubat, M., Holte, R. C., and Matwin, S. (1998b). Machine learning for the detection of oil spills in satellite radar images. *Mach. Learn.*, 30(2-3) :195–215.

[Kubat and Matwin, 1997] Kubat, M. and Matwin, S. (1997). Addressing the curse of imbalanced training sets : One-sided selection. In *ICML*, pages 179–186.

[Kumar and Spafford, 1994] Kumar, S. and Spafford, E. H. (1994). Ia pattern matching model for misuse intrusion detection. *Proceedings of the 17th National Computer Security Conference*, pages 11–21.

[Kwek and Nguyen, 2002] Kwek, S. and Nguyen, C. (2002). iboost : *Boosting* using an instance-based exponential weighting scheme. *thirteenth European Conference on Machine Learning*, pages 245–257.

[Lallich et al., 2007] Lallich, S., Lenca, P., and Vaillant, B. (2007). Construction of an off-centered entropy for supervised learning. In *XIIth International Symposium on Applied Stochastic Models and Data Analysis (AMSDA 07), Chania, Crete, Greece*.

[Lane and Brodley, 1998] Lane, T. and Brodley, C. E. (1998). Temporal sequence learning and data reduction for anomaly detection. *Proceedings of the Fifth ACM Conference on Computer and Communications Security*, pages 150–158.

[Lebbah and Bennani, 2010] Lebbah, M. and Bennani, Y. (2010). Sous-échantillonnage topographique par apprentissage semi-supervisé. *Proc. of the EGC'10*.

[LeBras et al., 2009] LeBras, Y., Lenca, P., and Lallich, S. (2009). On optimal rule mining : a framework and a necessary an sufficient condition of existence. In *Proceedings 13th Pacific-Asia Conference on Knowledge Discovery and Data Mining (PAKDD 09)*.

[Lee and Stolfo, 1998] Lee, W. and Stolfo, S. (Berkeley, CA, USA, 1998). Data mining approaches for intrusion detection. *In Proc. of the 7th USENIX Security Symposium (SECURITY-98)*, pages 79–94.

[Li, 2006] Li, J. (2006). On optimal rule discovery. *IEEE Transformation on Knowldge and Data Engeneering.*, 18(4) :460–471.

[Li and Jones, 2006] Li, J. and Jones, J. (2006). Using multiple and negative target rules to make classifiers more understandable. *Knowledge-Based Systems*, 19(6) :438–444.

[Li et al., 2001a] Li, J., Shen, H., and Topor, R. (2001a). Mining the smallest association rule set for predictions. *IEEE International Conference on Data Mining*, pages 361–368.

[Li and Zhang, 2003] Li, J. and Zhang, Y. (2003). Direct interesting rule generation. *IEEE International Conference on Data Mining*, pages 155–162.

[Li et al., 2001b] Li, W., Han, J., and Pei, J. (2001b). CMAR : Accurate and efficient classification based on multiple class-association rules. In *ICDM*, pages 369–376.

[Ling and Zhang, 2004] Ling, C. X., Q. Y. J. W. and Zhang, S. (2004). Decision trees with minimal costs. *Int. Conf. on Machine Learning*.

[Littlestone, 1987] Littlestone, N. (1987). Learning quickly when irrelevant attributes abound : A new linear-threshold algorithm. *Machine Learning*, 2 :285–318.

[Littlestone and Warmuth, 1994] Littlestone, N. and Warmuth, M. K. (1994). The weighted majority algorithm. In *Information and computation*, volume 24, pages 212–261.

[Liu et al., 1998] Liu, B., Hsu, W., and Ma, Y. (1998). Integrating classification and association rule mining. In *Knowledge Discovery and Data Mining*, pages 80–86.

[Mé et al., 2001] Mé, L., Marrakchi, Z., Michel, C., Debar, H., and Cuppens, F. (2001). La détection d'intrusions : les outils doivent coopérer. In *Revue de l'Electricité et de l'Electronique*, pages 5 : 50–55.

[Maclin, 1998] Maclin, R. (1998). *Boosting* classifiers regionally. *In AAAI/IAAI*, pages 700–705.

[Marcellin et al., 2006] Marcellin, S., Zighed, D.-A., and Ritschard, G. (2006). An asymmetric entropy measure for decision trees. In *11th Information Processing and Management of Uncertainty in knowledge-based systems (IPMU 06), Paris, France*, pages 1292–1299.

[McDonald et al., 2003] McDonald, R., Hand, D., and Eckley, I. (2003). An empirical comparison of three *Boosting* algorithms on real data sets with artificial class noise.

[Meir et al., 2000] Meir, R., El-Yaniv, R., and Ben-David, S. (2000). Localized *Boosting*. In *Proc. 13th Annu. Conference on Comput. Learning Theory*, pages 190–199. Morgan Kaufmann, San Francisco.

[Meir and Rätsch, 2003] Meir, R. and Rätsch, G. (2003). An introduction to *Boosting* and leveraging. pages 118–183.

[Mitchell, 1997] Mitchell, T. M. (1997). *Machine Learning*. McGraw-Hill, New York.

[Mukkamala et al., 2005] Mukkamala, S., Sung, A. H., and Abraham, A. (2005). Intrusion detection using an ensemble of intelligent paradigms. *J. Netw. Comput. Appl.*, 28(2) :167–182.

[Nock and Lefaucheur, 2002] Nock, R. and Lefaucheur, P. (2002). A robust *Boosting* algorithm. *In Thirteenth European Conference on Machine Learning*, pages 319–330.

[Pei et al., 2000] Pei, J., Han, J., and Mao, R. (2000). CLOSET : An efficient algorithm for mining frequent closed itemsets. In *ACM SIGMOD Workshop on Research Issues in Data Mining and Knowledge Discovery*, pages 21–30.

[Perner and Rosenfeld, 2003] Perner, P. and Rosenfeld, A., editors (2003). *Machine Learning and Data Mining in Pattern Recognition, Third International Conference, MLDM 2003, Leipzig, Germany, July 5-7, 2003, Proceedings*, volume 2734 of *Lecture Notes in Computer Science*. Springer.

[Pisetta et al., 2010] Pisetta, V., Jouve, P.-E., and Zighed, D.-A. (2010). Construction de noyaux pour l'apprentissage supervisé à partir d'arbres aléatoires. In *10ème Conférence Extraction et Gestion des Connaissances (EGC 2010), Hammamet, Tunisie*, volume E-19 of *Revue des Nouvelles Technologies de l'Information*, pages 525–536. Cépaduès.

[Provost, 2000] Provost, F. (2000). Machine learning from imbalanced data sets 101. *Invited paper for the AAAI'2000 Workshop on Imbalanced Data Sets*.

[Quinlan, 1986] Quinlan, J. R. (1986). Induction of decisions trees. *Machine Learning*, 1 :81–106.

[Quinlan, 1993] Quinlan, J. R. (1993). C4.5 : Programs for machine learning. *Morgan Kaufmann, San Mateo, CA*.

[Quinlan, 1994] Quinlan, J. R. (1994). Comparing connectionist and symbolic learning methods. *MIT Press*, 1 : Constraints and prospects(15) :445–456.

[Quinlan and Cameron-Jones, 1995] Quinlan, J. R. and Cameron-Jones, R. M. (1995). Induction of logic programs : FOIL and related systems. *New Generation Computing*, 13 :287–312.

[Ramadas and Tjaden, 2003] Ramadas, M. and Tjaden, S. (Pittsburgh, PA, USA, 2003). Detecting anomalous network traffic with self-organizing maps. *Proceedings of the 6th International Symposium on Recent Advances in Intrusion Detection*, pages 36–54.

[Riddle et al., 1994] Riddle, P., Segal, R., and Etzioni, O. (1994). Representation design and brute-force induction in a boeing manufacturing domain. *Applied Artificial Intelligence*, 8 :125–147.

[Ritschard, 2005] Ritschard, G. (2005). De l'usage de la statistique implicative dans les arbres de classification. *Jounrnées ASI'05*, 2(15) :305–315.

[Robnik-Sikonja, 2004] Robnik-Sikonja, M. (2004). Improving random forests. *European Conference on Machine Learning, Springer*, LNAI 3210 :359–370.

[Roesch, 2002] Roesch, M. (2002). Snort : The open source network intrusion system. *Official web page of Snort at http ://www.snort.org/*.

[Rosset et al., 2007] Rosset, S., Swirszcz, G., Srebro, N., and Zhu, J. (2007). l1 regularization in infinite dimensional feature spaces. In *Learning Theory : 20th Annual Conference on Learning Theory, volume 4539 of Lecture Notes in Computer Science*, pages 544–558. Springer-Verlag.

[Rätsch, 1998] Rätsch, G. (1998). Ensemble learning methods for classification. *Master's thesis,Dep of computer science, University of Potsdam*.

[Rätsch et al., 2001] Rätsch, G., Onoda, T., and Müller, K.-R. (2001). Soft margins for adaboost. *Mach. Learn.*, 42(3) :287–320.

[Rätsch and Warmuth, 2001] Rätsch, G. and Warmuth, M. K. (2001). Marginal *Boosting*. *NeuroCOLT2 Technical Report Series*.

[Rudin et al., 2004] Rudin, C., Daubechies, I., and Schapire, R. E. (2004). The dynamics of Adaboost : Cyclic behavior and convergence of margins. *Journal of Machine Learning Research*, 5 :1557–1595.

[Ryan et al., 1998] Ryan, J., Lin, M.-J., and Miikkulainen, R. (1998). Intrusion detection with neural networks. advances in neural information processing systems. *The MIT Press*.

[Saporta, 2001] Saporta, G. (2001). Data mining et statistique. *Journal de la Société Française de Statistique*, 140(1) :81–84.

[Schapire and Singer, 1999] Schapire, R. and Singer, Y. (1999). Improved *Boosting* algorithms using confedence rated predictions. *Machine Learning*, 37(3) :297–336.

[Sebastiani et al., 2000a] Sebastiani, F., Sperduti, A., and Valdambrini, N. (2000a). An improved *Boosting* algorithm and its application to automated text categorization. *In A. Agah, J. Callan, and E. Rundensteiner, editors, Proceedings of CIKM-00, 9th ACM International Conference on Information and Knowledge Management*, pages 78–85.

[Sebastiani et al., 2000b] Sebastiani, P., Ramoni, M., and Crea, A. (2000b). Profiling your customers using bayesian networks. *SIGKDD Explor. Newsl.*, 1(2) :91–96.

[Sebban and Suchier, 2003] Sebban, M. and Suchier, H.-M. (2003). Étude sur amélioration du *Boosting* : réduction de l'erreur et accélération de la convergence. *Journal électronique d'intelligence artificielle*.

[Servas et al., 2006] Servas, O., Dausque, N., Facq, A., Gazelle, F., and Feltin, G. (2006). Pourquoi et Comment Adapter une Politique de Sécurité pour les Entités du CNRS. Politique de Sécurité du Système d'Information.

[Servedio, 2001] Servedio, R. A. (2001). Smooth *Boosting* and learning with malicious noise. In *14th Annual Conference on Computational Learning Theory, COLT 2001 and 5th European Conference on Computational Learning Theory, EuroCOLT 2001, Amsterdam, The Netherlands, July 2001, Proceedings*, volume 2111, pages 473–489. Springer, Berlin.

[Shapire, 1990] Shapire, R. (1990). The strength of weak learnability. *Machine Learning*, 5 :197–227.

[Shon et al., 2005] Shon, T., Seo, J.-T., and Moon, J. (2005). SVM Approach with a Genetic Algorithm for Network Intrusion Detection. In *ISCIS*, pages 224–233.

[Shyu et al., 2003] Shyu, M.-L., Chen, S.-C., Sarinnapakorn, L., and Chang, K. (2003). A novel anomaly detection scheme based on principal component classifier. In *Proceedings of the IEEE Foundations and New Directions of Data Mining Workshop*, pages 172–179, Melbourne, FL, USA.

[Smaha and Haystack, 1988] Smaha, S. and Haystack (1988). An intrusion detection system. *in Proc. of the IEEE Fourth Aerospace Computer Security Applications Conference*, Orlando, FL :37–44.

[Srikant et al., 1997] Srikant, R., Vu, Q., and Agrawal, R. (1997). Mining association rules with item constraints. In *3rd International Conference on Knowledge Discovery and Data Mining*, pages 67–73.

[Stolfo et al., 1999] Stolfo, S. J., Fan, W., Lee, W., Prodromidis, A., and Chan, P. K. (1999). Cost-based modeling and evaluation for data mining with application to fraud and intrusion detection. *Results from the JAM Project.*

[Sun et al., 2006] Sun, Y., Wang, Y., and Wong, A. K. (2006). *Boosting* an associative classifier. *IEEE Transactions on Knowledge and Data Engineering*, 18(7) :988–992.

[Thabtah et al., 2004] Thabtah, F. A., Cowling, P., and Peng, Y. (2004). In *ICDM '04. Fourth IEEE International Conference on Data Mining.*

[Tibshirani, 1994] Tibshirani, R. (1994). Regression shrinkage and selection via the lasso. *Journal of the Royal Statistical Society, Series B*, 58 :267–288.

[Tomek, 1976] Tomek, I. (Nov. 1976). Two modifications of cnn. *IEEE Trans. Syst., Man, Cybern.*, SMC-6(11) :769–772.

[Torre, 2004] Torre, F. (2004). Globoost : *Boosting* de moindres généralisés. Technical report, GRAppA - Université Charles de Gaulle - Lille 3.

[Valdes and Skinner, 2000] Valdes, A. and Skinner, K. (2000). Adaptive, model-based monitoring for cyber attack detection. In Debar, H., Me, L., and Wu, F., editors, *Recent Advances in Intrusion Detection (RAID 2000)*, volume 1907 of *Lecture Notes in Computer Science*, pages 80–92, Toulouse, France. Springer-Verlag, Berlin—Heidelberg, Germany.

[van Rijsbergen, 1979] van Rijsbergen, C. J. (1979). *Information Retrieval.* Butterworths, London.

[Vapnik, 1995] Vapnik, V. (1995). *The Nature of Statistical Learning Theory.* Springer, New York.

[Vezhnevets and Vezhnevets, 2002] Vezhnevets, A. and Vezhnevets, V. (2002). Modest AdaBoost : Teaching AdaBoost to Generalize Better. *Moscow State University.*

[Visa,] Visa, S. Issues in mining imbalanced data sets - a review paper. In *in Proceedings of the Sixteen Midwest Artificial Intelligence and Cognitive Science Conference, 2005*, pages 67–73.

[Wang and Mendel, 1992] Wang, L.-X. and Mendel, J. ((1992)). Generating fuzzy rules by learning from examples. In *IEEE Trans. System, Man, and Cybernet*, pages 1414–1427.

[Wang et al., 2008] Wang, Y. J., Xin, Q., and Coenen, F. (2008). Hybrid rule ordering in classification association rule mining. *Transactions on Machine Learning and Data Mining*, 1(1) :1–15.

[Weiss and Provost, 2001] Weiss, G. and Provost, F. (11 January 2001). The effect of class distribution on classifier learning. Technical report, Department of Computer Science, Rutgers University.

[Weiss, 2004] Weiss, G. M. (2004). Mining with rarity : a unifying framework. *SIGKDD Explor. Newsl.*, 6(1) :7–19.

[Weiss et al., 2007] Weiss, G. M., McCarthy, K., and Zabar, B. (2007). Cost-sensitive learning vs. sampling : Which is best for handling unbalanced classes with unequal error costs ? In *DMIN*, pages 35–41.

[Weka update, 2006] Weka update (2006). Weka. URL http ://www.cs.waikato.ac.nz/˜ml/weka.

[Wilson and Martinez, 2000] Wilson, D. R. and Martinez, T. R. (2000). Reduction techniques for instance-based learning algorithms. *Machine Learning*, 38(3) :257–286.

[Wolpert, 1992] Wolpert, D. H. (1992). Stacked generalization. *Neural Networks*, 5 :241–259.

[Wuu et al., 2007] Wuu, L. C., Hung, C. H., and Chen, S. F. (2007). Building intrusion pattern miner for sonrt network intrusion detection system. *Journal of Systems and Software*, 80, Issue 10 :1699–1715.

[Ye et al., 2002] Ye, N., Emran, S., Chen, Q., and Vilbert, S. (2002). Multivariate statistical analysis of audit trails for host-based intrusion detection. *IEEE Transactions on Computers*, 51 :810–820.

[Yeung and Ding, 2003] Yeung, D. and Ding, Y. (2003). Host-based intrusion detection using dynamic and static behavioral models. 36(1) :229–243.

[Yin and Han, 2003] Yin, X. and Han, J. (2003). CPAR : Classification based on predictive association rules. In *3rd SIAM International Conference on Data Mining (SDM'03)*, pages 331–335, San Francisco, CA.

[Yoon and Lee, 2008] Yoon, Y. and Lee, G. G. (2008). Text categorization based on *Boosting* association rules. *International Conference on Semantic Computing*, pages 136–143.

[Yu and Hao, 2007] Yu, Y. and Hao, H. (2007). An ensemble approach to intrusion detection based on improved multi-objective genetic algorithm. *Journal of Software*, 18(6) :1369–1378.

[Zainal et al., 2009] Zainal, A., Maarof, M., and Shamsuddin, S. (2009). Ensemble classifiers for network intrusion detection system. *Journal of Information Assurance and Security*, 4 :217–225.

[Zaki, 2000] Zaki, M. J. (2000). Scalable algorithms for association mining. *IEEE Transactions on Knowledge and Data Engineering*, 12 :372–390.

[Zaki and Hsiao, 1999] Zaki, M. J. and Hsiao, C. (1999). Charm : An efficient algorithm for closed association rule mining. Technical report, Computer Science, Rensselaer Polytechnic Institute.

[Zhang and Mani, 2003] Zhang, J. and Mani, I. (2003). KNN approach to unbalanced data distributions : A case study involving information extraction. *In Proc. of the ICML workshop on learningfrom imbalanced datasets.*

[Zhang and Zulkernine, 2006] Zhang, J. and Zulkernine, M. (2006). Anomaly based network intrusion detection with unsupervised outlier detection. *Proc. of the IEEE ICC*, pages 2388–2393.

[Zhou and Liu, 2006] Zhou, Z.-H. and Liu, X.-Y. (2006). On multi-class cost-sensitive learning. *Nat. Conf. on Artificial Intelligence*, pages 567–572.

[Zighed and Rakotomalala, 2000] Zighed, D. and Rakotomalala, R. (2000). *Graphes d'induction apprentissage et data mining.* Hermès.